



Material Safety Data Sheet (MSDS) Report

MSDS Number: RF-SDS235

Applicant: Jiangsu Fengchi Green Power Co., Ltd.

No.82 Xinzhong Road, Xinzhuang Street, Yixing City, Jiangsu Province, 214200, China.

Sample Description:

Product name : Polymer Lithium-Ion Battery Pack
Product model : ITP2410
Nominal voltage : 24V
Typical capacity : 10000mAh/240Wh
Product weight : 2500g
Product dimension : L: 462mm, W: 81.5mm, T: 24mm
Data reviewed : Jan 10, 2019

Shanghai Ruifu Co., Ltd. did not test, certify, or approve the product described in this Material Safety Data Sheet (MSDS), and all information in this MSDS was provided by the applicant or was reproduced from publically available regulatory data sources. Shanghai Ruifu Co., Ltd. makes no representations or warranties regarding the completeness or accuracy of the information in this MSDS and disclaims all liability in connection with the use of this information or the product described in this MSDS. This MSDS was generated in accordance with requirements of OSHA Hazard Communication Standard 29 CFR 1910.1200 (OSHA HazCom 2012), for more details please refer to the following attached pages.

This report shall not be reproduced except in full, without the written approval of Shanghai Ruifu Co., Ltd.

Approved By:

Pingo Zhang, Manager

On behalf of Shanghai Ruifu Co., Ltd.

Shanghai Ruifu Co., Ltd.

Rm 22106, BLDG #1, NO.888 Huanhu Xi'Er Road, Pudong District, Shanghai, 201306, China

Tel: +86 21 67795598

E-mail: MSDS@vip.163.com

Website: www.msds-china.com

报告专用章

MATERIAL SAFETY DATA SHEET

Page: 1

Revision Date: 01/10/2019

SDS Number: RF-SDS235

Version: 3.0

Polymer Lithium-Ion Battery Pack

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product name : Polymer Lithium-Ion Battery Pack
Product model : ITP2410
Nominal voltage : 24V
Typical capacity : 10000mAh, 240Wh
Product weight : 2500g
Product dimension : L: 462mm, W: 81.5mm, T: 24mm

Recommended use of the chemical and restrictions on use

Identified use : Power supply for electronic device.

Details of the supplier of the safety data sheet

Jiangsu Fengchi Green Power Co.,Ltd
No.82 Xinzhong Road, Xinzhuang Street,
Yixing City, Jiangsu Province,
China

Emergency telephone number

Tel: +86-510-87560105 or contact your local
emergency center

Product Information

Tel: +86-510-87560105
E-mail: Chenpeng422@sina.com

SECTION 2. HAZARDS IDENTIFICATION

The battery is considered an article as defined by 29 CFR 1910.1200 (OSHA Hazard Communication Standard). The information contained in this MSDS is supplied at the customer's request for information only.

The following information is provided for the scenario that exposure occurred during battery production or container breakage or under extreme heat conditions such as fire, however, under normal conditions of battery use, internal ingredients/components will not present any physical, health and environmental hazard.

The following GHS classification are derived based on the internal ingredients/components under extreme scenarios, such as breakage, leakage or being abused.

Polymer Lithium-Ion Battery Pack

GHS-Classification

Hazard classification : Skin sensitisation, Category 1
May cause an allergic skin reaction.
Carcinogenicity, Category 2
Suspected of causing cancer.
Specific target organ toxicity - repeated exposure, Category 2,
Inhalation
May cause damage to organs through prolonged or repeated
exposure if inhaled.

GHS-Labeling

Symbol(s) : 

Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H373 May cause damage to organs through
prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have
been read and understood.
P210 Keep away from heat/sparks/open flames/hot
surfaces. No smoking.
P223 Do not allow contact with water.
P231 + P232 Handle under inert gas. Protect from moisture.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/
equipment.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/
spray.
P272 Contaminated work clothing should not be allowed
out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye
protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P308 + P313 IF exposed or concerned: Get medical advice/
attention.
P333 + P313 If skin irritation or rash occurs: Get medical
advice/ attention.
P335 + P334 Brush off loose particles from skin. Immerse in
cool water/ wrap in wet bandages.
P362 + P364 Take off contaminated clothing and wash it before
reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or
alcohol-resistant foam to extinguish.

MATERIAL SAFETY DATA SHEET

Page: 3

Revision Date: 01/10/2019

SDS Number: RF-SDS235

Version: 3.0

Polymer Lithium-Ion Battery Pack

Storage:

P402 + P404 Store in a dry place. Store in a closed container.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No further available information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product type : Manufactured article

Hazardous components

| Component | CAS Number | Percent of Total Weight |
|----------------------|----------------|-------------------------|
| Aluminum Foil | 7429-90-5 | 5% |
| Carbon(Graphite) | 7782-42-5 | 12-15% |
| Copper Foil | 7440-50-8 | 7-10% |
| Lithium Cobalt Oxide | 12190-79-3 | 2-3% |
| Lithium Salts | Not applicable | 1-5% |
| Nickel | 7440-02-0 | 2-5% |
| Organic Carbonate | Not applicable | 13-18% |

SECTION 4. FIRST AID MEASURES

Under normal conditions of battery use, internal ingredients/components will not present a health hazard. The following information is provided for exposures that may occur during battery production or container breakage or under extreme heat conditions such as fire.

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Move to fresh air.
If breathed in, move person into fresh air.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.
Wash contaminated clothing before re-use.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.

MATERIAL SAFETY DATA SHEET

Page: 4

Revision Date: 01/10/2019

SDS Number: RF-SDS235

Version: 3.0

Polymer Lithium-Ion Battery Pack

- If swallowed : Get medical attention immediately.
Do NOT induce vomiting.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray/Foam/Carbon dioxide (CO₂)/Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Toxic fumes, acrid smoke, irritating fumes.
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Normally not required.
In the event of fire and breakage, please ensure that:
Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

Polymer Lithium-Ion Battery Pack

Methods and materials for containment and cleaning up : If possible, carefully neutralize spilled electrolyte with soda ash, sodium bicarbonate, lime, etc.

Other information : Comply with all applicable national and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Use only approved chargers and procedures.
Improperly charging a cell may cause the cell or battery to flame or damage.
Do not drop battery, puncture, or attempt to open battery case.
Avoid contact with the internal components of a battery.
Do not subject product to open flame or fire and avoid situations that could cause arcing between terminals.
For personal protection see section 8.

Conditions for safe storage : Store batteries under roof in cool, dry, well-ventilated areas separated from incompatible materials and from activities that may create flames, spark, or heat.
Store sealed lead acid batteries at ambient temperature..
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
Store sealed batteries at ambient temperature.
Never recharge batteries in an unventilated, enclosed space.
Do not subject product to open flame or fire.
Avoid conditions that could cause arcing between terminals.

Personal protective equipment

Respiratory protection : None required for normal handling of the finished product.

Hand protection : None required for normal handling of the finished product.

Eye protection : None required for normal handling of the finished product.

Skin and body protection : None required for normal handling of the finished product.

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
Ensure that eyewash stations and safety showers are close to the workstation location.

MATERIAL SAFETY DATA SHEET

Page: 6

Revision Date: 01/10/2019

SDS Number: RF-SDS235

Version: 3.0

Polymer Lithium-Ion Battery Pack

When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Manufactured article

Colour : No data available

Odour : Odorless

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) :
No data available

Flammability (liquids) :
Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : Not applicable

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)
Water solubility : Insoluble

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Polymer Lithium-Ion Battery Pack

| | |
|----------------------|---------------------|
| Viscosity, dynamic | : Not applicable |
| Viscosity, kinematic | : No applicable |
| Oxidizing properties | : No data available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : Stable under recommended storage conditions. The sealed battery is considered stable. |
| Possibility of hazardous reactions | : Product will not undergo hazardous polymerization. |
| Incompatible materials | : None known. |
| Hazardous decomposition products | None under normal operating conditions. Carbon dioxide and hydrogen fluoride gas may be generated during combustion of battery. |

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: please refer to section 2.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information**Carcinogenicity:**

Polymer Lithium-Ion Battery Pack

| | |
|-------------|---|
| IARC | Cobalt in lithium cobalt oxide is considered as a class 2B carcinogen by IARC. |
| OSHA | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. |
| NTP | None Known to be human carcinogen |

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

When properly used or disposed, the batteries do not present environmental hazards.

Do not let internal components enter marine environment.

Avoid release to waterways, wastewater or groundwater.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Material should be recycled if possible.
The product should not be allowed to enter drains, water courses or the soil.
This material must be disposed of in a safe manner.
Send to a licensed waste management company.
Dispose of in accordance with all applicable national and local regulations.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

Lithium Ion Batteries are classified as Class 9 Dangerous Goods in the United Nations Recommendation. In case of transport, compliance with all the relevant UN regulations is required. This Polymer Lithium-Ion Battery Pack(Model: ITP2410, 24V, 10000mAh, 240Wh)has met the requirements of UN38.3 test(UN Manual of Tests and Criteria, Part III, Subsection 38.3.).

Lithium-ion batteries (limited to a maximum of 30% SoC) are subject to the following transport rules:

MATERIAL SAFETY DATA SHEET

Polymer Lithium-Ion Battery Pack

| Method | Technical Guidelines | Packing Instruction and Special |
|--------|---|---|
| Air | 2019-2020 Edition of the ICAO Technical Instruction for the Safe Transport of Dangerous Goods by Air (Technical Instructions) and the 60th Edition of the IATA Dangerous Goods Regulations (DGR). | Packing Instruction 965(PI965, section IA) IMP: RBI Limit per package: Pax A/C = Forbidden/CAO = 35 kg |
| Sea | IMDG Code 2019(38-16) | Special Provision 188, 230, 310, 348, 376, 377,384 |

Provisions for the international transportation (pursuant to ICAO-TI/IATA-DGR, IMDG Code):

UN-No.: UN 3480

Proper Shipping Name: Lithium Ion Batteries

IMDG 2019(38-16)


| | |
|----------------------------|-----------------------|
| UN Number | UN3480 |
| UN Proper shipping name | Lithium ion batteries |
| Transport hazard class(es) | 9 |
| Packing Group | N/A |

IATA 2018 (60th Edition of the IATA Dangerous Goods Regulations (DGR))

| | |
|-------------------------|-----------------------|
| UN Number | UN3480 |
| UN Proper shipping name | Lithium ion batteries |
| Hazard Class | 9 |
| Packing Group | N/A |

ADR

| | |
|-------------------------|-----------------------|
| UN Number | UN3480 |
| UN Proper shipping name | Lithium ion batteries |
| Hazard Class | 9 |
| Packing Group | N/A |



Note: All lithium ion cells and batteries shipped by themselves (UN 3480) are forbidden for transport as cargo on passenger aircraft. All packages prepared in accordance with Packing Instruction 965, Section IA, IB and II, must bear a Cargo Aircraft Only label, in addition to existing marks and/or labels.

SECTION 15. REGULATORY INFORMATION

SARA 302 : Not listed.

MATERIAL SAFETY DATA SHEET

Page: 10

Revision Date: 01/10/2019

SDS Number: RF-SDS235

Version: 3.0

Polymer Lithium-Ion Battery Pack

SARA 311/312 Hazards : Not regulated.

SARA 313 Component(s) Cobalt compounds are considered hazardous and are subjected to reporting requirements of section 313 title III of the superfund amendments and reauthorization act of 1986 (SARA) and 40 CFR part 372.

California Prop 65 This product does not contains any chemical known to the State of California to cause cancer.

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 10/01/2019

Disclaimer:

This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of our knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. We assumed no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

End of Report
